

## DS-PT1-WB



- 433MHz two-way wireless communication
- AES-128 encryption
- LED display, show the different feedbacks with easy understanding
- Operation: Stay arm/away arm/disarm by areas
- Arming process with fault confirm, more secure
- Patrol tag check in
- Front and rear panel tamper-proof

## ▪ Specification

Hardware features	
Power switch	Power on/off
Electrical characteristics	
Battery type	Three AA batteries
Operation humidity	10% to 90% (no condensing)
Operation temperature	-10°C to +55°C (-4°F to +122°F)
Power consumption	Quiescent current: 110 uA Max current: 292mA Voltage: 1.5 VDC
Battery life span	Up to 2 years (standby time)
Wireless transmission	
RF frequency	433 MHz
RF modulation	2GFSK
RF distance	900m(open area)
Display	
Indicator	5, area(blue), fault(orange), arm(blue), disarm(green), alarm(red), signal(red/green)
General	
Installation method	Wall mounting
Dimension(WxHxD)	75*124*21 mm
Color	white
Weight	176g (with battery)

## ▪ Available Model

DS-PT1-WB

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

