



MAXHUB UC S15

Ultra-Wide Angle, All-in-One Collaboration Videobar for Huddle & Small Rooms

The MAXHUB UC S15 is a 4K wide-angle BYOD Videobar with an outstanding acoustic solution, as well as a meeting platform for huddle and small meeting rooms. With a simple interface, a single-click launcher, and a plethora of collaborative tools, it's a breeze to get started. In addition, UC S15's BYOM integration with WT13M makes it simple to share content, as well as the device's built-in camera, microphone, and speakers.




Ultra HD 4K

Exceptional UHD video quality



120° FOV

Provides full-room coverage



Auto Framing

AI Vision
Intelligent face detection




BYOM

Wireless content and camera, microphone, and speaker sharing



Voice Localization

Speaker tracking
Voice tracking



PoE

PoE support that simplifies installation and minimizes cost



Built-in System

Agnostic meeting platform



PIR Sensor

Auto on/off
Completely hands-free and energy saving

Camera

Pixel	12 M		
Sensor	1/2.3-inch 12 MP Sony sensor		
ZOOM	5x Digital Zoom		
Resolution and Frame Rate:			
MJPEG/H264:	(1) 3840 x 2160	(2) 2560 x 1440	(3) 1920 x 1080
	(4) 1280 x 720	(5) 1024 x 576	(6) 960 x 540
	(7) 800 x 600	(8) 640 x 480	(9) 640 x 360
	(10) 480 x 270	(11) 352 x 288	(12) 320 x 240
	(13) 320 x 180		
NV12/YUY2	(1) 1920 x 1080	(2) 1280 x 720	(3) 640 x 360
Output Format	H.264; YUY2; MJPG		
Field of View	FOV 120° (D)		
Adjustable Angle	±15° (V)		
Focus Mode	Fixed-Focus		
Focus Distance	1m		
Special Features	① Auto Framing: automatic FOV adjustment to fit in all participants; ② Speaker Tracking: voice triggered people tracking; ③ 3 zoom presets to instantly set up the conference		

Audio**Speaker**

Sound Channel	1.1
Output Power	8 W + 3 W
Maximum Sound Pressure	83 dB SPL@1 m
Signal to Noise Ratio	>75 dB
Frequency Range	150 Hz ~ 18 kHz

Microphone

Quantity	6
Voice Pickup Range	100 Hz~7.5 kHz
Microphone Frequency Range	100 Hz ~ 7.5 kHz
Special Features	Noise Reduction, Echo Cancellation, Anti-Reverberation, Built-in AGC Algorithm

PIR Sensor

In power-on mode, the device automatically enters standby mode If no moving object is detected within 3 meters for 30 minutes, minimizing energy consumption.

In standby mode, the device automatically starts up on detecting moving objects within 3 meters, simplifying the setup process.

Input/Output Port

USB 3.0 Type-C	Connect USB host, upgrade system, etc.
USB 3.0 Type-A	Flash drive, keyboard, mouse, etc.
USB 2.0 Type-A	Flash drive, keyboard, mouse
AUDIO OUT	Used for external audio equipment
HDMI OUT	HDMI 2.0, supports 280*720p, 1920*1080p, 3840*2160p, supports CEC
DC 2.0	Used for 12 V power input power supply
RJ45	IP support, PoE power support

Power

Power Requirements	12 V
Standby mode power consumption	≤ 0.5 W
PoE Power	Yes (IEEE 802.3af or 802.3at)

Operating System

System Version	Android 9.0
RAM	4 G
ROM	16 G
CPU	2×A72+4×A53

Wi-Fi

Wi-Fi Protocol	802.11ac/n/g/b/a/ax
Working Band	2.4 GHz; 5 GHz
Working Mode	AP+STA
Working Distance	0~10 m

Bluetooth

Version	5.0
Protocol	A2DP;HFP;HSP;AVRCP;BLE
Working Distance	0~10 m

Mount

- Wall-mount
- TV mount kit (Optional)

Physical Specifications

Dimension L×H×W	462×76×93 mm (18.2x3.0x3.7 inch)
Dimension (package) L×W×H	1 pc: 538x160x169 mm (21.2x6.3x6.7 inch) 4pcs: 628x433x380 mm (24.7x17.0x15.0 inch)
Net Weight	1.20 kg (2.65 lb)
Gross Weight	1 pc: 2.74 kg (6.04 lb) 4 pcs: 12.90 kg (28.44 lb)

Environmental Conditions

Operation Temperature	0 °C~40 °C
Operation Humidity	10%~90%RH
Storage Temperature	-20 °C~60 °C
Storage Humidity	10%~90%RH
Below 5000 meters	

Application Supported

- MAXHUB Meeting OS
- MAXHUB Share
- MAXHUB Pivot
- MAXHUB Share
- Whiteboard

Compatibility

Supports major VC software including ZOOM, Microsoft® Teams, Google Meet, Google Hangouts, Cisco WebEx®, RingCentral, etc.

Warranty

- 3 Years hot-swap
- Accessories 1 year

Compatible BYOM Dongle

MAXHUB WT13M

What's in the box

- HDMI Cable 1.5 m (59.1 inch)
- USB 3.0 Cable 1.8 m (70.87 inch)
- USB 2.0 Cable 3 m (118.11 inch)
- Lens Cover
- Wall-mounted Components
- Power Adapter
- Remote Control
- User Manual



MAXHUB
Beyond Collaboration

