

MAXHUB

The V6 Classic Series

MAXHUB Collaboration Display

Refine Meeting Efficiency



Total Solution, Minimal Setup

A complete, seamless design fulfills every meeting requirement, including built-in camera, mic, and touch panel. Whether video conferencing or hosting a local discussion, it's as easy as plugging in your power cable.



Distinguish Every Detail in Ultra-HD

Experience 1.07 billion colors in brilliant detail with high-color gamut and ultra-HD, 4K display, promising a professional-grade image quality. Zero-bonding technology effectively reduces air refraction and parallax for enhanced visual clarity.

Advanced, Intuitive Video Conferencing

Experience next-level video conferencing with a wide field of vision, and crystal-clear, amplified audio. Thanks to auto-framing, the V6 Classic Series intuitively adjusts to the number of meeting participants and their location.

Sony 1/2-inch Sensor 92° HFOV WDR



Auto-Framing



Speaker-Tracking



Exceptional Voice Clarity

8 non-equidistant microphone arrays, Built-in AI noise reduction, 2.1 channel stereo sound, 2x10W+20W (subwoofer) seam speakers.



Easy, Wireless Screen-sharing

The V6 Classic Series' dual Wi-Fi modules simultaneously support a screen-sharing hotspot and Wi-Fi network connection.



Syncs Perfectly with Your Devices

The V6 Classic Series' front-facing Type-C interface design allows you to cast from and control your own devices through the touchscreen.



Prioritizing Healthcare

Antibacterial glass, antibacterial passive styluses, and an antibacterial power button keeps you safe.



Effortless Access with MAXHUB OS 6.0

Users can personalize the customizable homepage for a tailored user experience, and join a scheduled meeting with just one click.

Specification

Camera	C5530	C6530	C7530	C8630
Model	C5530	C6530	C7530	C8630
Diagonal Size(inch)	55	65	75	86
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Response Time	8ms	8ms	8.5ms	8ms
Brightness(typ)	350cd/m ²	350cd/m ²	350cd/m ²	350cd/m ²
Contrast Ratio	1200 : 1	1200 : 1	5000 : 1	4000 : 1
Color Gamut(typ)	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Touch System				
Touch	IR Touch	IR Touch	IR Touch	IR Touch
Max Touch Points Supported	20	20	20	20
Accuracy	±1mm	±1mm	±1mm	±1mm
Object Recognition Range	≥2mm	≥2mm	≥2mm	≥2mm
Glass	Zero Parallax, 3mm Angi-glare, Antibacterial	Zero Parallax, 3mm Angi-glare, Antibacterial	Zero Parallax, 3mm Angi-glare, Antibacterial	Zero Parallax, 3mm Angi-glare, Antibacterial
Connectivity				
Input	HDMI IN x1, USB 2.0 x1, USB 3.0 x2, TOUCH 2.0 x1, USB Type-C x 2	HDMI IN x1, USB 2.0 x1, USB 3.0 x2, TOUCH 2.0 x1, USB Type-C x 2	HDMI IN x1, USB 2.0 x1, USB 3.0 x2, TOUCH 2.0 x1, USB Type-C x 2	HDMI IN x1, USB 2.0 x1, USB 3.0 x2, TOUCH 2.0 x1, USB Type-C x 2
Audio	Audio out x1	Audio out x1	Audio out x1	Audio out x1
OPS Slot	Yes, 3840 x 2160@60fps	Yes, 3840 x 2160@60fps	Yes, 3840 x 2160@60fps	Yes, 3840 x 2160@60fps
Camera&Audio&Microphone				
Built-in Camera	48MP Single Camera	48MP Single Camera	48MP Single Camera	48MP Single Camera
Camera Features	Auto-Framing / Speaker-Tracking	Auto-Framing / Speaker-Tracking	Auto-Framing / Speaker-Tracking	Auto-Framing / Speaker-Tracking
Built-in Speakers	2.1 Channel, 10W x 2 + 20W	2.1 Channel, 10W x 2 + 20W	2.1 Channel, 10W x 2 + 20W	2.1 Channel, 10W x 2 + 20W
Microphone Array	8x Far-field, Max 8m Range	8x Far-field, Max 8m Range	8x Far-field, Max 8m Range	8x Far-field, Max 8m Range
Features				
Ambient light sensor	Yes	Yes	Yes	Yes

V6 Classic Series

The Classic series is MAXHUB's most popular Interactive Flat Panel for meetings, collaboration and presentations for our corporate partners. Fulfilling the need for a device which can host remote meetings and local discussions for all sizes of organization from start-up teams to multinational companies.

MAXHUB V6 Classic Series of IFP brings together all the functions a meeting room needs, such as wireless screen sharing, whiteboarding, presenting as well as video conferencing with a high-quality camera and a wide microphone range. Every meeting room should have a MAXHUB V6 Classic series to enhance teamwork and increase organizational efficiency.



Professional 4K Display

High Color Accuracy, $\Delta E \leq 2$
Wide Color Gamut, NTSC 90%



Touch Screen

20 Touch Points,
Minimum Object Recognition - 2mm



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle



Smart Whiteboard

OCR supported,
Multiple built-in templates



Built-in Camera

48million pixels
Offer the best view in both dark/bright
scene with WDR technology



10th Gen Intel CPU

Powerful performance, fluid experience
* With use of MAXHUB PC Module



Built-in Microphone

8 meters of voice pick-up
8 mics arrays, clear conversations



Built-in Speaker

2.1 Channel
2x 10W + 20W

Display

Model / Part No.	C5530	C6530	C7530	C8630
Diagonal Size (inch)	55	65	75	86
Backlight	Direct-lit LED	Direct-lit LED	Direct-lit LED	Direct-lit LED
Panel Technology	IPS	IPS	VA	VA
Aspect Ratio	16 : 9	16 : 9	16 : 9	16 : 9
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Response Time	8ms	8ms	8.5ms	8ms
Brightness (typ)	350cd/m ²	350cd/m ²	350cd/m ²	350cd/m ²
Contrast Ratio	1200 : 1	1200 : 1	5000 : 1	4000 : 1
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°
Color Gamut (typ)	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Display Orientation	Landscape	Landscape	Landscape	Landscape
Operating Hour	16/7	16/7	16/7	16/7

Dimension&Weight

Product Dimensions (WxHxD)	1263 x 776 x 88 mm 49.72 x 30.55 x 3.46 inch	1488 x 903 x 88 mm 58.58 x 35.55 x 3.46 inch	1709 x 1026 x 87 mm 73.35 x 44.88 x 8.86 inch	1957.1 x 1160.1 x 100.2 mm 77.05 x 45.67 x 3.94 inch
Shipping Dimensions (WxHxD)	1392 x 847 x 220mm 54.8 x 33.35 x 8.66 inch	1638 x 1005 x 208mm 64.09 x 39.57 x 8.19 inch	1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inch	2110 x 1283 x 225 mm 83.07 x 50.51 x 8.86 inch
Net Weight (kg /pounds)	26.25kg / 57.87 lbs	36.25kg / 79.92 lbs	48.3kg / 106.48 lbs	59.75kg / 131.73 lbs
Gross Weight (kg /pounds)	34.2kg / 75.40 lbs	46.75kg / 103.07 lbs	62.8kg / 138.45 lbs	77.00kg / 169.76 lbs
Wall Mount (VESA)	400 x 200mm / 15.75 x 7.78inch	600 x 400mm / 23.62 x 15.75inch	800 x 400mm / 31.50x15.75inch	800 x 600mm / 31.50 x 23.62inch
Screws For VESA	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch

POWER

Power Supply	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz
Max Power Consumption	300W	350W	400W	400W
Standby	≤0.5W	≤0.5W	≤0.5W	≤0.5W

Touch System

Touch Sensor	IR Touch
Max Touch Points Supported	20
Accuracy	±1mm
Object Recognition Range	≥2mm
Glass	Zero parallax , 3mm Angi-glare, Antibacterial
Supported Operating System (Touch Return)	Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS

Connectivity

Input	HDMI IN x 1 , USB 2.0 x 1, USB 3.0 x 2, TOUCH 2.0 x 1 , USB Type-C x 2
Audio	Audio out x 1
Control	RS232 x 1
PC Module Slot	Yes, 3840 x 2160@60fps
PC Module	MAXHUB PC Module
Wifi Module	SI06

Camera/Audio/Microphone

Built-in Camera	Yes, Single Camera, 48MP
Camera Features	Auto Frame / Speaker Tracking
Built-in Speakers	2.1 Channel , 2x10W+20W
Microphone Array	8 x Far-field , beam-forming microphone - max 8m range

Environment

Operating Temperature	0 C~40 C
Storage Temperature	10%~90%RH
Operating Humidity	-20 C~60 C
Storage Humidity	10%~90%RH

What's In The Box

Standard Power Cord, 1 x Wifi Adapter, 2 x Passive Stylus, 1 x Wall Mount, 1 x Type-C Cable (1.8m | 70.9inch)

Optional



wireless dongle



ST41B



ST23C



EST09



EST11