

APC Smart-UPS 48V 585 Wh LI Battery Pack XBP48RM1U-LI



- Includes: 4 post rail kit, Communication cable, Grounding cable, Installation guide, Rack mounting brackets

Output

| | |
|------------------------|------|
| Battery Output Voltage | 48 V |
|------------------------|------|

Batteries & Runtime

| | |
|--------------|----------------------|
| Battery type | Li-Ion (Lithium-Ion) |
|--------------|----------------------|

| | |
|------------------|------------|
| Battery mounting | Rack mount |
|------------------|------------|

| | |
|-------------------------------|--------|
| Expected Battery Life (years) | 5 - 10 |
|-------------------------------|--------|

Physical

| | |
|----------------|-------------|
| Maximum Height | 43MM, 4.3CM |
|----------------|-------------|

| | |
|---------------|---------------|
| Maximum Width | 432MM, 43.2CM |
|---------------|---------------|

| | |
|---------------|---------------|
| Maximum Depth | 521MM, 52.1CM |
|---------------|---------------|

| | |
|-------------|----|
| Rack Height | 1U |
|-------------|----|

| | |
|------------|---------|
| Net Weight | 13.02KG |
|------------|---------|

| | |
|-----------------|---------|
| Shipping weight | 18.64KG |
|-----------------|---------|

| | |
|-----------------|---------------|
| Shipping Height | 200MM, 20.0CM |
|-----------------|---------------|

| | |
|----------------|---------------|
| Shipping Width | 600MM, 60.0CM |
|----------------|---------------|

| | |
|----------------|---------------|
| Shipping Depth | 850MM, 85.0CM |
|----------------|---------------|

| | |
|-------|-------|
| Color | Black |
|-------|-------|

| | |
|------------------|-----|
| Units per Pallet | 8.0 |
|------------------|-----|

Environmental

| | |
|-----------------------|-----------|
| Operating Temperature | 0 - 40 °C |
|-----------------------|-----------|

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

| Environmental | |
|-----------------------------|---------------------------|
| Operating Relative Humidity | 0 - 95 (Non-condensing) % |
| Operating Elevation | 0 - 3048meters |
| Storage Temperature | -15 - 45 °C |
| Storage Elevation | 0 - 15240meters |

| Conformance | |
|-------------------|--------------------------|
| Approvals | UL 1973 |
| Standard warranty | 5 year repair or replace |

| Sustainable Offer Status | |
|--------------------------|-----------|
| RoHS | Compliant |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.