

USB-C HYBRID ACTIVE OPTICAL CABLES

C-U32-LLRA-CC-x



USB 3.2 Right-Angled Type C to C Hybrid Active Optical Cable

C-U32-LL-CC-x



USB 3.2 Type C to C Hybrid Active Optical Cable

C-U32-LLF-CC-x



USB 3.2 Full Featured Type C to C Hybrid Active Optical Cable

C-U32-LL-AC-x



USB 3.2 Type A to C Hybrid Active Optical Cable

PRODUCT CODE	LENGTH	DOWNWARD COMPATIBILITY	BANDWIDTH	VIDEO RESOLUTION	POWER DELIVERY	WORKING TEMPERATURE	CABLE OUTER DIAMETER	JACKET OUTER MATERIAL	CERTIFICATE (COMPLIANCE & TESTING)
C-U32-LLRA-CC-10	10M	USB 2.0 / 1.1	10Gbps	-	5V 800mA	-20°C to 80°C	4.8 mm	PVC / CMP / CPR	CE / FCC / RoHS / REACH / UKCA
C-U32-LLRA-CC-15	15M	USB 2.0 / 1.1	10Gbps	-	5V 800mA	-20°C to 80°C	4.8 mm	PVC / CMP / CPR	CE / FCC / RoHS / REACH / UKCA
C-U32-LL-CC-10	10M	USB 2.0 / 1.1	10Gbps	-	5V 800mA	-20°C to 80°C	4.8 mm	PVC / CMP / CPR	CE / FCC / RoHS / REACH / UKCA
C-U32-LL-CC-15	15M	USB 2.0 / 1.1	10Gbps	-	5V 800mA	-20°C to 80°C	4.8 mm	PVC / CMP / CPR	CE / FCC / RoHS / REACH / UKCA
C-U32-LLF-CC-10	10M	USB 2.0 / 1.1	10Gbps	8K@60Hz	10M: 60W 15M: 40W	-20°C to 80°C	6.5 mm	TPE	CE / FCC / RoHS / REACH / UKCA
C-U32-LLF-CC-15	15M	USB 2.0 / 1.1	10Gbps	8K@60Hz	10M: 60W 15M: 40W	-20°C to 80°C	6.5 mm	TPE	CE / FCC / RoHS / REACH / UKCA
C-U32-LL-AC-10	10M	USB 2.0 / 1.1	10Gbps	-	5V 800mA	-20°C to 80°C	4.8 mm	PVC / CMP / CPR	CE / FCC / RoHS / REACH / UKCA
C-U32-LL-AC-15	15M	USB 2.0 / 1.1	10Gbps	-	5V 800mA	-20°C to 80°C	4.8 mm	PVC / CMP / CPR	CE / FCC / RoHS / REACH / UKCA

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at contactus@dynamix.co.nz

Last updated: 22 October 2025