

HIGH PERFORMANCE FAN HEATER

DESCRIPTION

The DYNAMIX compact high-performance fan heater prevents the formation of condensation and provides evenly distributed interior air temperature in enclosures with electrical/electronic components. The plastic enclosure provides double insulation and protection against contact. The fan heater is available with an integrated thermostat or pre-set hygrostat for temperature or humidity control. The REHEAT-400W is designed to be fixed at the bottom of the enclosure.

FEATURES

- Compact design
- Double insulated
- Integrated thermostat or hygrostat



PRODUCT CODE	HEATING CAPACITY	OPERATING VOLTAGE	SETTING RANGE	WEIGHT
RAHEAT-400W	400W	230Vac, 50/60Hz	0 to 60°C	1.40 kg

SPECIFICATIONS

Heating element:	High-performance cartridge
Temperature safety cut-out:	Protects against overheating in case of fan failure
Heater body:	Extruded aluminium profile
Connection:	2-pole max. 2.5mm ² , clamping screw with strain relief (Max. tightening torque 0.8 Nm)
Casing:	Plastic according to UL94 V-0, black
Mounting:	Screw fixing (M5)
Fitting position:	Horizontal
Dimensions:	167 × 150 × 100 mm
Operating / Storage temperature:	-45 to +70°C (-49 to 158°F)
Protection type / Protection class:	IP20 / II (Double insulated)
Approvals:	CE

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at contactus@DYNAMIX.co.nz

Last updated: 26 FEBRUARY 2026



TECH DRAWINGS

