UNITEK

Human friendly

Triple Display USB4 40Gbps Docking Station (D1117AGY)

Supports 40Gbps Data Transfer & 2.5Gbps Network.

Description: UNITEK Triple Display USB4 40Gbps Docking Station features one full-feature USB-C 40 Gbps port (with video output), three 10 Gbps (2C1A) ports, two 5 Gbps (1C1A) ports, two HDMI outputs, a 2.5G Ethernet port, a SD 4.0 card slot, a microSD 3.0 card slot, and a 3.5mm audio/mic. jack. It provides stable connectivity with efficient heat dissipation to meet users' daily needs. Additionally, it is compatible with Thunderbolt 4 for seamless connectivity with a variety of devices.

Product Features:

- **Triple Displays Output:** Boost productivity with Triple 4K/ Dual 8K + 4K monitor output. Windows Single display supports up to 8K@60Hz via USB-C port/ 8K@30Hz via HDMI port. Dual display supports up to 8K@30Hz via USB-C and HDMI port. The docking station features MST capability (Windows only) and is perfect for creative professionals, gamers, and multitaskers.

- **Power Delivery Capabilities:** UNITEK Triple Display USB4 40Gbps Docking Station is equipped with three power delivery ports: the host USB-C port supports PD of max 85W output, the 40Gbps full-feature USB-C port supports up to 15W DC output, and the PD port supports up to 20W. This setup fulfills the charging needs for laptops, cell phones, and tablets.

- **Full feature USB4 port:** Transfer data at 40 Gbps, drive high-resolution displays with support for a maximum of 8K at 60Hz, and supports a 15W DC output for device charging. This docking station delivers enhanced performance through USB4 compatibility (Compatible with Thunderbolt 4).

- **Multi-port Data transfer:** 3 ports (1A2C) at 10 Gbps and 2 ports (1A1C) at 5 Gbps. Built-in SD 4.0 and microSD 3.0 slots provide easy access to files from universal SD and microSD memory cards, supporting simultaneous reading of both cards.

- **High-Speed & Stable Ethernet** The 2.5G Ethernet port supports and is compatible with 1000 / 100 / 10 Mbps network transmission.

Note: Different devices with various versions of Type-C Host DP Alt Mode have varying output capabilities.

Dimensions	183.0mm x 82.0mm x 21.6mm
Upstream	USB4 40Gbps (Compatible with Thunderbolt 4 and max PD85W output)
Downstream	1 x 40G full-feature USB-C Port (including Video + DC15V output); 3 x USB (1A2C) 10Gbps port; 2 x USB (1A1C) 5Gbps port; 1 x HDMI 8K@30Hz; 1 x HDMI 4K@60Hz; 1 x PD20W Port. 1 x SD4.0 & MicroSD3.0; 1 x 3.5mm Audio/ Mic. jack; 1 x 2500Mbps Network
Windows Output Resolution	**Single** USB4: 8k@60Hz; HDMI Single: 8k@30Hz or 4k@60Hz **Dual** 1) USB-C: 8k@30Hz + HDMI 8k@30Hz 2) USB-C: 8k@30Hz + HDMI 4k@60Hz 3) HDMI Dual: 8k@30Hz/4k@120Hz + 4k@60Hz **Triple** USB-C: 8k@30Hz/4k@120Hz + HDMI: 8k@30Hz/4k@120Hz + 4k@60Hz
macOS Output Resolution	**Single/ Dual/ Triple** 4k@60Hz
DC Power	20.0V/6A 120W Power Adapter
Material/ Colour	Aluminium Alloy/ Space Grey

Package Contents: 1 x Triple Display USB4 40Gbps Docking Station; 1 x 0.8M USB4 C-C Cable; 1 x 120W Power Adapter; 1 x User Manual.

Pieces/ Carton: 5 pieces/ carton